



APPLY THIN FILLET BEAD OF SEALANT TO TOP OF RETAINER BAR-BLEND INTO SEISMIC COLORSEAL CORNER BEAD

SANTOPRENE SHEET CORNER-PIECE CONNECTS DECK & WALL FLANGES

TWO-PART POLYURETHANE NOSING MATERIAL REINFORCED WITH SAND & FIBER

EMSEAL SEISMIC COLORSEAL PRECOMPRESSED FOAM SEALANT

BOOT TERMINATION WITH TRANSITION TO EMSEAL SEISMIC COLORSEAL IN VERTICAL PLANE

PERFORATED FLANGES ENCAPSULATED IN NOSING MATERIAL

EMSEAL THERMAFLEX TCR MULTI-BARRIER HEAT WELDABLE SANTOPRENE GLAND

**EMSEAL JOINT SYSTEMS LTD.**

THERMAFLEX TCR DECK TO WALL SEISMIC COLORSEAL BOOT TERMINATION

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE UNAVAILABLE TO THE PUBLIC AND IS PROPRIETARY TO EMSEAL CORPORATION. ANY UNAUTHORIZED USE, WILL BE PROSECUTED. REPRODUCTION IN ANY FORM BEING THE EXCLUSIVE RIGHT OF EMSEAL CORPORATION. ANY UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE DIMENSIONS WILL BE PROSECUTED.

DRAWN	DATE:	SCALE:	DRAWING
BY: WAJ	10/14/04	N.T.S.	No: 1 OF 1
PART NUMBER:			